



**YOUR PROTECTION
BY EXCELLENCE**

RIPACK 2500
THE LIGHTEST IN ITS CATEGORY



For regular shrink wrapping needs, the Ripack 2500 is the ideal tool for protecting your pallets. With adjustable power, it will adapt to the thickness of your films.

Compact and light, the Ripack 2500 is equipped with «cold nozzle» technology for unparalleled safety.

With its innovative quick and tool-free igniter change system, benefit from a reliable and robust shrink gun.

These heat tools are used in many sectors such as industry, construction, food, transport / logistics ...

TECHNICAL SPECIFICATIONS

Power	34 to 60 kW
Pressure	1,5 to 3,5 bars
Gas consumption	from 2,2 to 4 kg/h
Length/Height	14,17"/10,32" - 360/262 mm
Package dimensions	460x330x140 mm 18,11" x 13" x 5,51"
Weight	33,16 oz / 940 g
Package weight	10,76 lb / 4880 g
Noise level	< 85 dbA
Energy source	Propane gas or natural gas upon request




Each gun is delivered in a carrying case with: 1 SECURIPACK 1.5-3.5 bar gas regulator, 1 8-meter hose with crimped connection, 1 key for tightening/untightening the connections, 1 user manual with CE certificate.


EQUIPMENT SOLD SEPARATELY AND IN KIT



**936 GAS BOTTLE
TROLLEY**



GAS HOSE REEL



**MANUAL SEALER
MULTICOVER 955**



Please refer to the regulations applicable in the country of use concerning the conformity and use of the products and accessories offered in our Ripack® range. All information and photos in this brochure refer to product specifications updated at the time of publication according to the date mentioned on this page. RIPACK® reserves the right to change the colors, materials, features and specifications of its products at any time. Some products may be shown with accessories and/or features not available in some countries. All rights reserved. Reproduction in any form and by any means is prohibited without previous authorization from RIPACK®.

* guarantee for labor and parts; www.ripack.com

www.ripack.com

